



## **General Filter Care**

## Follow these simple filter care instructions for ALL filters except for Sundance MicroClean II filters (for 2006+ 800 models) and Hot Spring Tri-X models.

- Standard paper filters have a life expectancy of 1 ½ 2 years if cared for properly. Maintenance for filters depends on the water care system you are currently using:
- <u>Baqua Spa</u>: For tubs on the BaquaSpa chemical system, follow the 2x2 system. Every TWO weeks, remove your filter(s) and rinse with water. Every TWO months, soak your filter(s) overnight in the BaquaSpa filter cleaning solution.
- <u>Nature II/Chlorine</u>: For tubs on the nature II/chlorine (or bromine) system, the filters should be soaked in Brilliance for spas filter cleaner every time you drain your spa.

## Please note that the small white micro clean filter for older Sundance spas and current 780 series Sundance spas MUST be replaced every 3-4 months!

| power to tub.<br>the filter lid.<br>any debris from the filter compartment. (This is important because if debris<br>way into internal plumbing, blockage could result).<br>the filter retainer (located on the top of the filter standpipe).<br><b>Do not remove the filter standpipe while removing the retainer. If the</b><br><b>e is inadvertently unscrewed while removing the filter retainer,</b> |
|--|
| any debris from the filter compartment. (This is important because if debris<br>way into internal plumbing, blockage could result).<br>the filter retainer (located on the top of the filter standpipe).<br><b>Do not remove the filter standpipe while removing the retainer. If the</b><br><b>e is inadvertently unscrewed while removing the filter retainer,</b>                                     |
| way into internal plumbing, blockage could result).<br>the filter retainer (located on the top of the filter standpipe).<br>Do not remove the filter standpipe while removing the retainer. If the<br>e is inadvertently unscrewed while removing the filter retainer,   |
| the filter retainer (located on the top of the filter standpipe).<br>Do not remove the filter standpipe while removing the retainer. If the<br>e is inadvertently unscrewed while removing the filter retainer,  |
| Do not remove the filter standpipe while removing the retainer. If the e is inadvertently unscrewed while removing the filter retainer,  |
| e is inadvertently unscrewed while removing the filter retainer,   |
|  |
|  |
| tely separate the two components and reinstall the standpipe. The spa  |
| er be operated without the standpipe in place.   |
| the filters.   |
| all the filters, reverse steps 1 to 4.   |
| Do not over-tighten filter retainer! Over tightening of the filter retainer<br>It in removal of the filter standpipe during the next filter removal.   |
| t  |

If you have further questions, don't hesitate to call your local Spring Dance store:

www.SpringDanceHotTubs.com relax@springdancehottubs.com